

## SHEEN MAGIC® Hydrocarbon Sheen Remover

This concentrated, multipurpose and unique cleaner of hydrocarbon contaminants far exceeds the efficiency of the products normally used in hydrocarbon sheen remediation.

**PLUTUS SHEEN-MAGIC®** neutralizes hydrocarbon based oil and grease sheens by molecular conversion into harmless, non-toxic compounds. These compounds are consumed by naturally occurring microbes that are always found in water. The resultant runoff is water soluble and is safe for disposal in sanitary sewers, soil, or open seas.

**NOTE:** *State and Local Regulations should always be reviewed in order to determine what can be discharged into municipal sewer systems.*

### USES FOR PLUTUS SHEEN-MAGIC®

**PLUTUS SHEEN-MAGIC®** is very effective solution for removal of sheens resulting from:

- ◆ Petroleum/crude oil fill racks
- ◆ Oil and water separators
- ◆ Storage tank & pipeline exterior surfaces including valves, manifolds and railings
- ◆ Manufacturing or fabrication processes or spills
- ◆ Maintenance & repair facility floors
- ◆ Parking or storage lot runoff
- ◆ Fuel spills and traffic accident cleanup

**PLUTUS SHEEN-MAGIC®** is cost and time effective for remediation of all hydrocarbon sheens. In case of a major spill **PLUTUS SHEEN-MAGIC®** may be safely disposed of in drain or storm sewer without danger to the public or the environment.

### APPLICATION INSTRUCTIONS

#### — GENERAL HARD SURFACE CLEANUP —

**Step 1.** Before beginning any treatment process make sure all SAFETY GUIDELINES and PROCEDURES are in place. If in doubt about correct procedure, then check with SAFETY OFFICER or OSHA before proceeding. PLUTUS Environmental Technologies, Inc. or its associated or subsidiary companies shall not be held liable or at risk for any safety violations or errors by the user. Always wear an appropriate mask and glasses when applying any spray solution.

- Step 2.** Recover all standing hydrocarbons possible for disposal or recycling. Hydrocarbons often collect in depressions or spalled areas. These areas should be wiped with an absorbent pad, rag or wipe before application of PLUTUS SHEEN-MAGIC®.
- Step 3.** Apply PLUTUS SHEEN-MAGIC® with sprayer.
- Step 4.** PLUTUS SHEEN-MAGIC® will instantly break down and remove the sheen upon application.
- Step 5.** If an unacceptable amount of sheen remains repeat Steps 2-4 until satisfactory.

#### — HYDROCARBON SHEENS ON WATER —

- Step 1.** Before beginning any treatment process make sure all SAFETY GUIDELINES and PROCEDURES are in place. If in doubt about correct procedure, then check with SAFETY OFFICER or OSHA before proceeding. PLUTUS Environmental Technologies, Inc. or its associated or subsidiary companies shall not be held liable or at risk for any safety violations or errors by user.
- Step 2.** Recover all hydrocarbons possible. Recoverable hydrocarbons should be boomed, wiped or vacuumed for recycling before application of PLUTUS SHEEN-MAGIC®. If these volume amounts can be removed for disposal or recycling then the volume of application of PLUTUS SHEEN-MAGIC® will be reduced.
- Step 3.** Small sheens may be treated by using a hand sprayer. Larger sheens may require aerial application or spray delivery from boat or barge mounted delivery systems. Aerial delivery should be at speed that produce droplet shear as per nozzle manufacturer specifications.
- Step 4.** PLUTUS SHEEN-MAGIC® will instantly break down and remove the sheen upon application.
- Step 5.** Repeat Steps 1-5 until desired level is achieved.
- NOTE:** PLUTUS SHEEN-MAGIC® works in any weather situation or temperature condition when a spray application may be used to deliver the product to the sheen area.

For Technical Assistance call (865) 776-8343